



**Fisherbrand**  
QUALITY. RELIABILITY. VALUE.

Centrifugation

Mini and Midi Centrifuges

# Mini Centrifuge

The Fisherbrand Mini Centrifuge is ideal for quick spin downs, micro-filter cell separations, PCR\* and HPLC samples. It is compact and easy to use and comes as standard with a host of accessories



## Key features & benefits:

- Small footprint and quiet operation
- UV resistant housing
- SnapSpin™ rotors for quick and easy change
- Compact ergonomic design and footprint
- Max speed 6,000rpm/2,000xg
- Weighted rubberised base eliminates potential movement and further dampens any noise output
- One year warranty

## Technical Specification

Capacity rotor 1	6 x 1.5/2mL tubes
Capacity rotor 2	2 x 8 0.2mL strips or 16 single tubes
Adapters for rotor 1	6 x 0.5mL and 6 x 0.2mL tubes
Speed range, rpm;	6,000
RCF:	2,000xg
Dimensions:	153 x 128 x 104mm
Electrical requirements:	220-230V, 50/60Hz

Cat. No	Description
15358266	Mini centrifuge, includes rotors, tube rack, storage case, O-rings, tube adapters and low voltage, double insulated power adapter with four interchangeable plugs

For the full range of Fisherbrand products, visit [www.eu.fishersci.com/go/fisherbrand](http://www.eu.fishersci.com/go/fisherbrand)

\*PCR is a registered trademark of Hoffmann LaRoche Inc



# Midi Centrifuge

Achieve maximal speed with minimum space. The Fisherbrand Midi Centrifuge is ideal for protocols calling for fast spins with a higher RCF requirement. Ideal for micro-filter cell separations, PCR\*, clinical applications and HPLC protocols

## Key features & benefits:

- Compact footprint and brush-less motor for quiet operation and low vibration
- Select and set the digital speed display in RCF or RPM
- Sample imbalance and tilt safety cut-out
- Safety interlock lid prevents opening while rotor is turning
- Back lit display showing time, speed and operational information on the same screen
- Quick spin button for short spin requirements
- UV resistant plastic, increased useful life under harsh light conditions
- Push-button lid release
- Manual override allows user to open lid in case of power failure
- Two year warranty

## Supplied with two rotors:

- 12 place standard rotor with lid for 1.5/2.0mL tubes
- Eight place strip rotor for four 0.2mL tube strips or 32 single tubes



### Technical Specification

Speed range, rpm;	500 to 12,500
RCF:	15 to 9,800xg
Dimensions:	203 x 171 x 114mm
Electrical requirements:	100-240V, 50/60Hz

Cat. No.	Description
12972041	Midi centrifuge, includes rotors, 12 x 0.2mL and 12 x 0.5mL tube adapters, universal double insulated power adapter with four interchangeable plugs